

Termék adatlap

DULUX F 18 W/840 2G10

OSRAM DULUX F | Flat CFLni, 2 tubes, with 4-pin base for ECG/CCG operation



Termék adatlap

Műszaki adatok

Elektromos adatok

ZLDV_Nominal current [AGGR]	0.38 A A
-----------------------------	----------

Fotometriai adatok

ZLDV_Light color (designation) [AGGR]	LUMILUX Cool White
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.86
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.83
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.81
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.77
ZLDV_Luminous flux [AGGR]	1100 lm
Színvisszaadási index Ra	≥80

Méretetek és súly

ZLDV_Overall length [AGGR]	128.00 mm
ZLDV_Tube diameter [AGGR]	17,5 mm
ZLDV_Length with base excl. base pins/connection [AGGR]	121,0 mm
ZLDV_Product weight [AGGR]	69.15 g

Hőmérséklet és működési feltételek

ZLDV_Ambient temperature range [AGGR]	-5...+40 °C
---------------------------------------	-------------

Élettartam

ZLDV_Service life [AGGR]	9000 h
Névleges élettartam	13000 h

További termékadatokat

Termék adatlap

ZLDV_Mercury content [AGGR]	2.5 mg
Ártalmatlanítás WEEE szerint	Yes

Tanúsítványok és szabványok

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	18.00 kWh/1000h

Ország-specifikus kategorizálás

ZLDV_ILCOS [AGGR]	FSD-18/840-E-2G10-90/122
-------------------	--------------------------

Környezetvédelmi információk

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300333526
Declaration No. in SCIP database	In work

Light Distribution

FL_840

Termék adatlap

Equipment / Accessories

- Suitable for operation on electronic and conventional control gear

SERIES CONNECTION WITH QUICKTRONIC

SINGLE LAMP WITH QUICKTRONIC

SERIES CONNECTION TO 230V ONLY WITH STARTER
ST151

SINGLE LAMP STARTER ST 111 OR ST 171

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
-----------	------------------	------------------------------	--	----------	-------------

Termék adatlap

4050300333526	DULUX F 18 W/840 2G10	Karton 10 Pieces Folding Box	280 mm x 100 mm x 150 mm	4.20 dm ³	994.00 g
---------------	--------------------------	------------------------------------	-----------------------------	----------------------	----------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to
▶ www.osram.hu/QUICKTRONIC

Lemondás

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

DULUX F 18 W/840 2G10

OSRAM DULUX F | Flat CFLni, 2 tubes, with 4-pin base for ECG/CCG operation

Product name	Product name ECG	EAN	Névleges teljesítmény + veszteség	Nominal current	Luminous flux at 35 °C	Number of lighting outlets
DULUX F 18 W/840 2G10	QT-ECO 1x18-24/220-240 S	4050300638560	18.00 W	0.13 A	1000 lm	1
	QTi DALI 2x18 DIM	4050300870526	37.00 W	0.16 A	1100 lm	2
	QTi DALI 3x18 DIM	4008321069979	53.60 W	0.24 A	1100 lm	3
	QTP-M 1x26-42	4008321329134	19.00 W	0.09 A	1050 lm	1
	QTP-OPTIMAL 1x18-40	4008321873743	18.00 W	0.08 A	1050 lm	1
	QTP-OPTIMAL 2x18-40	4008321873767	33.00 W	0.16 A	1050 lm	2

Product name	Product name ECG	EAN	EEI – Energy Label (prod. comb.)
DULUX F 18 W/840 2G10	QT-ECO 1x18-24/220-240 S	4050300638560	A2
	QTi DALI 2x18 DIM	4050300870526	
	QTi DALI 3x18 DIM	4008321069979	
	QTP-M 1x26-42	4008321329134	
	QTP-OPTIMAL 1x18-40	4008321873743	
	QTP-OPTIMAL 2x18-40	4008321873767	