

# Termék adatlap

## DULUX T/E PLUS 26 W/830

OSRAM DULUX T/E PLUS | CFLni, 3 tubes, with 4-pin base for ECG operation



# Termék adatlap

## Műszaki adatok

### Elektromos adatok

|                             |          |
|-----------------------------|----------|
| ZLDV_Nominal current [AGGR] | 0.33 A A |
|-----------------------------|----------|

### Fotometriai adatok

|                                       |                    |
|---------------------------------------|--------------------|
| ZLDV_Light color (designation) [AGGR] | LUMILUX Warm White |
| ZLDV_Rated LLMF at 4,000 h [AGGR]     | 0.84               |
| ZLDV_Rated LLMF at 6,000 h [AGGR]     | 0.83               |
| ZLDV_Rated LLMF at 8,000 h [AGGR]     | 0.81               |
| ZLDV_Rated LLMF at 12,000 h [AGGR]    | 0.79               |
| ZLDV_Rated LLMF at 16,000 h [AGGR]    | 0.78               |
| ZLDV_Rated LLMF at 20,000 h [AGGR]    | 0.9                |
| ZLDV_Luminous flux [AGGR]             | 1750 lm            |

### Méretetek és súly

|                                                         |           |
|---------------------------------------------------------|-----------|
| ZLDV_Overall length [AGGR]                              | 131.50 mm |
| ZLDV_Length with base excl. base pins/connection [AGGR] | 116,00 mm |
| ZLDV_Product weight [AGGR]                              | 62.5 g    |

### Hőmérséklet és működési feltételek

|                                       |             |
|---------------------------------------|-------------|
| ZLDV_Ambient temperature range [AGGR] | -5...+40 °C |
|---------------------------------------|-------------|

### Élettartam

|                          |         |
|--------------------------|---------|
| ZLDV_Service life [AGGR] | 13000 h |
|--------------------------|---------|

### További termékadatok

|                             |        |
|-----------------------------|--------|
| ZLDV_Mercury content [AGGR] | 2.0 mg |
|-----------------------------|--------|

Termék adatlap

|                              |                        |
|------------------------------|------------------------|
| Ártalmatlanítás WEEE szerint | Yes                    |
| ZLDV_Product remark [AGGR]   | For ECG operation only |

Tanúsítványok és szabványok

|                                     |                 |
|-------------------------------------|-----------------|
| ZLDV_Energy efficiency class [AGGR] | G               |
| ZLDV_Energy consumption [AGGR]      | 28.00 kWh/1000h |

Ország-specifikus kategorizálás

|                   |                         |
|-------------------|-------------------------|
| ZLDV_ILCOS [AGGR] | FSMH-26/830-/P/-GX24q-3 |
|-------------------|-------------------------|

Környezetvédelmi információk

|                                                                       |               |
|-----------------------------------------------------------------------|---------------|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |               |
| Date of Declaration                                                   | 18-04-2022    |
| Primary Article Identifier                                            | 4050300342306 |
| Declaration No. in SCIP database                                      | In work       |

Light Distribution

FL\_830

# Termék adatlap

## Equipment / Accessories

- Suitable for operation on electronic control gear

SERIES CONNECTION WITH QUICKTRONIC QT-DE

SINGLE LAMP WITH QUICKTRONIC QT-DE

## Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

## Logisztikai adatok

| Termékkód     | Termékmegnevezés           | Csomagolás<br>(darab/egység)       | Méreték (hosszúság<br>x szélesség x<br>magasság) | Térfogat             | Bruttó súly |
|---------------|----------------------------|------------------------------------|--------------------------------------------------|----------------------|-------------|
| 4050300342306 | DULUX T/E PLUS 26<br>W/830 | Karton<br>10 Pieces Folding<br>Box | 260 mm x 105 mm x<br>159 mm                      | 4.34 dm <sup>3</sup> | 1117.00 g   |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

For more information on QUICKTRONIC electronic control gear go to  
▶ [www.osram.hu/QUICKTRONIC](http://www.osram.hu/QUICKTRONIC)

Lemondás

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany

# DULUX T/E PLUS 26 W/830

OSRAM DULUX T/E PLUS | CFLni, 3 tubes, with 4-pin base for ECG operation

| Product name            | Product name ECG        | EAN           | Névleges teljesítmény + veszteség | Nominal current | Fényáram 25 °C-on | Number of lighting outlets |
|-------------------------|-------------------------|---------------|-----------------------------------|-----------------|-------------------|----------------------------|
| DULUX T/E PLUS 26 W/830 | QT-M 2x26-42/220-240 S  | 4008321110022 | 54.00 W                           | 0.23 A          | 1800 lm           | 2                          |
|                         | QTP-M 1x26-42           | 4008321329134 | 27.00 W                           | 0.12 A          | 1750 lm           | 1                          |
|                         | QTP-T/E (1x26-42), 2x26 | 4008321537089 | 54.00 W                           | 0.24 A          | 1750 lm           | 2                          |
|                         | QTP-T/E 1x26-42, (2x26) | 4008321537089 | 28.00 W                           | 0.13 A          | 1750 lm           | 1                          |

| Product name            | Product name ECG        | EAN           | EEI – Energy Label (prod. comb.) |
|-------------------------|-------------------------|---------------|----------------------------------|
| DULUX T/E PLUS 26 W/830 | QT-M 2x26-42/220-240 S  | 4008321110022 |                                  |
|                         | QTP-M 1x26-42           | 4008321329134 |                                  |
|                         | QTP-T/E (1x26-42), 2x26 | 4008321537089 |                                  |
|                         | QTP-T/E 1x26-42, (2x26) | 4008321537089 |                                  |