

Termék adatlap

DULUX D/E 18 W/830

OSRAM DULUX D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



Műszaki adatok

Elektromos adatok

ZLDV_Nominal current [AGGR]	0.22 A A
-----------------------------	----------

Fotometriai adatok

ZLDV_Light color (designation) [AGGR]	LUMILUX Warm White
ZLDV_Rated LLMF at 2,000 h [AGGR]	0.9
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.84
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.82
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.81
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.79
ZLDV_Rated LLMF at 16,000 h [AGGR]	0.78
ZLDV_Rated LLMF at 20,000 h [AGGR]	0.78
ZLDV_Luminous flux [AGGR]	1200 lm

Méreték és súly

ZLDV_Overall length [AGGR]	146.00 mm
ZLDV_Length with base excl. base pins/connection [AGGR]	130,00 mm
ZLDV_Product weight [AGGR]	37.5 g

Hőmérséklet és működési feltételek

ZLDV_Ambient temperature range [AGGR]	-5...+40 °C
---------------------------------------	-------------

Élettartam

ZLDV_Service life [AGGR]	13000 h
--------------------------	---------

További termékadatok

Termék adatlap

ZLDV_Mercury content [AGGR]	1.6 mg
Ártalmatlanítás WEEE szerint	Yes

Tanúsítványok és szabványok

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	19.00 kWh/1000h

Ország-specifikus kategorizálás

ZLDV_ILCOS [AGGR]	FSQH-18/830-/P/-G24q-2
-------------------	------------------------

Környezetvédelmi információk

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300327211
Declaration No. in SCIP database	In work

Light Distribution

FL_830

Termék adatlap

Equipment / Accessories

- Suitable for operation on electronic control gear

SERIES CONNECTION WITH QUICKTRONIC QT-DE

SINGLE LAMP WITH QUICKTRONIC QT-DE

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méreték (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4050300327211	DULUX D/E 18 W/830	Karton 10 Pieces Folding Box	186 mm x 81 mm x 171 mm	2.58 dm ³	569.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to
▶ www.osram.hu/QUICKTRONIC

Lemondás

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

DULUX D/E 18 W/830

OSRAM DULUX D/E | CFLni, 2 tubes, with 4-pin base for ECG operation

Product name	Product name ECG	EAN	Névleges teljesítmény + veszteség	Nominal current	Fényáram 25 °C-on	Number of lighting outlets
DULUX D/E 18 W/830	QTP-T/E (1X18), 2X18	4008321537065	36.00 W	0.16 A	1200 lm	2
	QTP-T/E 1X18, (2X18)	4008321537065	19.00 W	0.09 A	1*1200 lm	1