

Termék adatlap

HQI-TS 70 W/NDL

POWERSTAR HQI-TS EXCELLENCE | Fémhalogén lámpák kvarc technológiával



Műszaki adatok

Elektromos adatok

ZLDV_PFC capacitor at 50 Hz [AGGR]	12 µF
ZLDV_Ignition voltage [AGGR]	13.3 kVp
ZLDV_Nominal current [AGGR]	0.95 A A

Fotometriai adatok

ZLDV_Rated LLMF at 2,000 h [AGGR]	0.92
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.9
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.85
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.78
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.73
ZLDV_UV protection [AGGR]	Yes
ZLDV_Luminous flux [AGGR]	6100 lm

Méreték és súly

ZLDV_Light center length (LCL) [AGGR]	57,0 mm
ZLDV_Product weight [AGGR]	17.00 g
ZLDV_Overall length [AGGR]	117.00 mm

Hőmérséklet és működési feltételek

ZLDV_Maximum permitted pinch temperature [AGGR]	350 °C
---	--------

Élettartam

ZLDV_Lifespan B50 [AGGR]	12000 h
--------------------------	---------

További termékadatok

ZLDV_Design / version [AGGR]	Clear
------------------------------	-------

Termék adatlap

ZLDV_Mercury content [AGGR]	10.6 mg
Ártalmatlanítás WEEE szerint	Yes

Képességek

ZLDV_Burning position [AGGR]	p45
ZLDV_Enclosed luminaire required [AGGR]	Yes
ZLDV_Hot restart [AGGR]	Yes

Tanúsítványok és szabványok

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	83.00 kWh/1000h

Ország-specifikus kategorizálás

ZLDV_ILCOS [AGGR]	MD/UB-70/842-H/E/SL-RX7s-19/117/H
-------------------	-----------------------------------

Környezetvédelmi információk

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	30-06-2022
Primary Article Identifier	4008321678324
Declaration No. in SCIP database	In work

System guarantee

For the vast majority of our lamps we are offering an extended system guarantee in conjunction with OSRAM POWERTRONIC control gear.

OPERATION OF HIGH INTENSITY DISCHARGE LAMPS
WITH SEMI-PARALLEL IGNITION UNIT

OPERATION OF HIGH INTENSITY DISCHARGE LAMPS
WITH A SUPERIMPOSED IGNITION UNIT

OPERATION OF HIGH INTENSITY DISCHARGE LAMPS
WITH PULSE IGNITION UNIT

ELEKTRONIC OPERATION OF HIGH INTENSITY
DISCHARGE LAMPS

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4008321678324	HQI-TS 70 W/NDL	Karton 12 Pieces Folding Box	149 mm x 116 mm x 135 mm	2.33 dm ³	410.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system guarantee and the terms and conditions of the guarantee visit [https://
www.inventronics-light.com/multilevel-guarantees](https://www.inventronics-light.com/multilevel-guarantees)

Lemondás

A változtatás jogát fenntartjuk. Hibák és mulasztások kizárva. Mindig győződjön meg arról, hogy a legújabb kiadást használja.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

HQI-TS 70 W/NDL

POWERSTAR HQI-TS EXCELLENCE | Fémhalogén lámpák kvarc technológiával

Product name	Product name ECG	EAN
HQI-TS 70 W/NDL	PTi 70/220-240 I	4008321099501