

HMI double-ended



A termék jellemzői


- Color temperature: approx. 6,000 K (Daylight)
- High color rendering index: $R_a >$
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Hot restart capability




Termékcsalád adatlap




340667_HMI 6000W DXS



340671_HMI 12000W DXS



340677_HMI 18000W DXS



340682_HMI 24000W DXS

Termékcsalád adatlap

Műszaki adatok

Termékmegnevezés	Elektromos adatok			Fotometriai adatok			Méretek és súly
	Névleges feszültség	Névleges áram	Gyújtási feszültség, hideg/meleg	Névleges fényáram	Színhőmérséklet	Színvisszaadási index	Átmérő
HMI 575 W/DXS	950 V	7 A		49000 lm	6000 K	90	210 mm
HMI 1200 W/DXS	100 V	1380 A		110000 lm	6000 K	> 90	270 mm
HMI 2500 W/S XS	115 V	256 A		240000 lm	6000 K	90	315 mm
HMI 2500 W/DXS	115 V	256 A	20/45 kVp ¹⁾	240000 lm	6000 K	90	315 mm
HMI 4000 W/DXS	200 V	240 A	20/65 kVp	380000 lm	6000 K	90	360 mm
HMI 4000 W/DXS SOLAR	201 V	2400 A		395000 lm	7000 K	>90	360 mm
HMI 6000 W/DXS	122 V	550 A		570000 lm	6000 K	90	540 mm
HMI 12000 W/DXS	240 V	84 A		1150000 lm	6000 K	90	64.0 mm
HMI 18000 W/DXS	380 V	79 A		1700000 lm	6000 K	> 90	700 mm
HMI 24000 W/DXS	280 V	90 A		2300000 lm	6000 K	> 90	830 mm

Termékmegnevezés	Hosszúság	Szerelési hosszúság	Elektróda rész, hideg	Élettartam	Környezetvédelmi információk Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
				Élettartam	Date of Declaration
HMI 575 W/DXS	1350 mm	115,0 mm		1000 h	05-03-2024
HMI 1200 W/DXS	2200 mm	180,0 mm		1000 h	05-03-2024
HMI 2500 W/S XS	2100 mm	150,0 mm		500 h	05-03-2024
HMI 2500 W/DXS	3550 mm	290,0 mm	14,0 mm	500 h	05-03-2024
HMI 4000 W/DXS	4050 mm	340,0 mm	34,0 mm	500 h	05-03-2024
HMI 4000 W/DXS SOLAR	4050 mm			500 h	06-03-2024
HMI 6000 W/DXS	4500 mm			500 h	05-03-2024
HMI 12000 W/DXS	470.0 mm			500 h	05-03-2024
HMI 18000 W/DXS	5000 mm		44,0 mm	500 h	05-03-2024
HMI 24000 W/DXS	5000 mm			375 h	05-03-2024

Termékmegnevezés	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database	CAS No. of substance 1
HMI 575 W/DXS	4050300932071 4008321285102	No declarable substances contained	In work	

Termékcsalád adatlap

Termékmegnevezés	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database	CAS No. of substance 1
HMI 1200 W/DXS	4050300932088 4008321931153	No declarable substances contained	In work	
HMI 2500 W/S XS	4050300025780	No declarable substances contained	No declarable substances contained	
HMI 2500 W/DXS	4050300932095 4008321182197	No declarable substances contained	In work	
HMI 4000 W/DXS	4050300932101 4008321210203	No declarable substances contained	In work	
HMI 4000 W/DXS SOLAR	4052899152601	No declarable substances contained	No declarable substances contained	
HMI 6000 W/DXS	4050300932118 4008321210210	Lead	473650a6-c144-4760-a4f0-5f7779e0d7fe	7439-92-1
HMI 12000 W/DXS	4008321210227	Lead	9bbbe108-6929-4ec2-90c3-f2313bf610cc	7439-92-1
HMI 18000 W/DXS	4008321370280 10046135542135	Lead	f14371f4-413d-4982-a113-e8e17de542e0	7439-92-1
HMI 24000 W/DXS	4008321355805	Lead	e6c82c15-550e-4821-97a3-8abf917baea6	7439-92-1

		Képességek	
Termékmegnevezés	Safe Use Instruction	Hűtés	
HMI 575 W/DXS			
HMI 1200 W/DXS			
HMI 2500 W/S XS			
HMI 2500 W/DXS		Konvekció	
HMI 4000 W/DXS		Konvekció	
HMI 4000 W/DXS SOLAR			
HMI 6000 W/DXS	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
HMI 12000 W/DXS	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
HMI 18000 W/DXS	The identification of the Candidate List substance is sufficient to allow safe use of the article.	Konvekció	

Termékcsalád adatlap

		Képességek
Termékmegnevezés	Safe Use Instruction	Hűtés
HMI 24000 W/DXS	The identification of the Candidate List substance is sufficient to allow safe use of the article.	Konvekció

1) Max. 55 kV

Termékcsalád adatlap

Biztonsági tanács

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Használati tanácsok

További részletes alkalmazási információkat és grafikákat a termék adatlapján talál.

Lemondás

A változtatás jogát fenntartjuk. Hibák és mulasztások kizárva. Mindig győződjön meg arról, hogy a legújabb kiadást használja.