

HTI

Fémhalogén lámpák, egy végén fejelt



A termék előnyei

- High luminance
- High luminous efficacy and efficiency



Termékcsalád adatlap

Műszaki adatok

Termékmegnevezés	Elektromos adatok		Fotometriai adatok				
	Névleges feszültség	Névleges áram	Névleges fényáram	Fénysűrűség	Színhőmérséklet	Színvisszaadási index	Luminous efficacy
HTI 150 W ¹⁾	950 V	16 A	9500 lm	5000 cd/cm ²	6500 K	70	67 lm/W
HTI 152 W	900 V	17 A		4200 cd/cm ²	5000 K	> 80	67 lm/W
HTI 705 W/SE XS ²⁾	700 V	1000 A	57500 lm	30000 cd/cm ²	5500 K	80	85 lm/W
HTI 1200 W/SE XS ²⁾	950 V	1380 A	105000 lm	26000 cd/cm ²	5400 K	> 90	85 lm/W
HTI 2500 W/SE XS ³⁾	105 V	238 A	240000 lm	30000 cd/cm ²	6000 K	90	95 lm/W

Termékmegnevezés	Méretek és súly			Élettartam	További termékadatok	Képességek
	Átmérő	Hosszúság	Fénypontmagasság (LCL)	Élettartam	Lámpafej (szabványos megjelölés)	Égetési helyzet
HTI 150 W ¹⁾	2000 mm	460 mm	30,0 mm	750 h	GY9.5	Tetszőleges
HTI 152 W	2000 mm	480 mm	30,0 mm	2000 h	GY9.5	Tetszőleges
HTI 705 W/SE XS ²⁾	2400 mm ⁴⁾	850 mm	39,0 mm	500 h	GY9.5	p4 ⁵⁾
HTI 1200 W/SE XS ²⁾	2900 mm ⁴⁾	1350 mm	59,0 mm	750 h	GY22 ⁶⁾	Other ⁵⁾
HTI 2500 W/SE XS ³⁾	3300 mm	1800 mm	85,0 mm	600 h	G22 ⁷⁾	Other

Termékmegnevezés	Környezetvédelmi információk Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database	Candidate List Substance 1
HTI 150 W ¹⁾	05-03-2024	4050300301402 4050300932194	In work	
HTI 152 W	05-03-2024	4050300461519	In work	
HTI 705 W/SE XS ²⁾	05-03-2024	4050300618074	No declarable substances contained	No declarable substances contained
HTI 1200 W/SE XS ²⁾	05-03-2024	4050300371153	No declarable substances contained	No declarable substances contained
HTI 2500 W/SE XS ³⁾	05-03-2024	4050300371146	3978605c-1e11-462a-9ec2-94ccc12ef473	Lead

Termékmegnevezés	CAS No. of substance 1	Safe Use Instruction
HTI 150 W ¹⁾		
HTI 152 W		
HTI 705 W/SE XS ²⁾		
HTI 1200 W/SE XS ²⁾		

Termékcsalád adatlap

Termékmegnevezés	CAS No. of substance 1	Safe Use Instruction
HTI 2500 W/SE XS ³⁾	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.

1) Horizontal arc

2) SE = Single ended/XS = eXtreme Seal (maximum permissible foil temperature 450 °C)

3) Special GY22 base. The ignition voltage may be applied only to the thin pin/XS = eXtreme Seal (maximum permissible foil temperature 450 °C)/Important: The contact pins of the base are short-circuited; the electrode farthest from the base is connected via cable

4) Bura árambevezetővel

5) Árambevezető lent

6) Special GY22 base. The ignition voltage may be applied only to the thin pin

7) Important: The contact pins of the base are short-circuited; the electrode farthest from the base is connected via cable

Termékcsalád adatlap

Biztonsági tanács

Because of their high luminance, UV radiation and high internal pressure during operation, HTI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Használati tanácsok

További részletes alkalmazási információkat és grafikákat a termék adatlapján talál.

Lemondás

A változtatás jogát fenntartjuk. Hibák és mulasztások kizárva. Mindig győződjön meg arról, hogy a legújabb kiadást használja.