OSRAM

LEDriving PX-5

LED daytime running light for retrofit





LED pixel technology

Dynamic appearance thanks to faceted optic and dotted pixel technology



DRI

LED daytime running light compatible with a wide range of car models and easy to install



5200 K

For drivers who want to increase visibility during the day



Stylish highlights for your car

LEDriving PX-5 serves as a high performance and energy-efficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

Product family datasheet

Technical data

| | General Product Information | Electrical Data | | Photometric Data |
|---------------------|--------------------------------|-----------------|-----------------|-------------------|
| Product description | Global order reference | Nominal voltage | Nominal wattage | Color temperature |
| LEDriving PX-5 | LEDDRL301 | 12 V | 12 W | 5200 K |
| LEDriving PX-5 | LEDDRL301 | 12 V | 12 W | 5200 K |

| Product description | Nominal luminous flux | Physical Attributes & Dimensions Length | Lifetime Data Guarantee | Additional product data Connector to lamp |
|---------------------|--------------------------|--|-------------------------------|--|
| LEDriving PX-5 | 300 lm | 160.0 mm | 3 years | Wire Kit |
| LEDriving PX-5 | 550 lm | 160.0 mm | 3 years | Wire Kit |

| | Capabilities | Certificates & standards | | Logistical data |
|---------------------|--------------|---------------------------|-----------|-----------------|
| Product description | Technology | Approval marks – approval | Standards | Commodity code |
| LEDriving PX-5 | LED | E4 approval | ECE R87 | 85122000900 |
| LEDriving PX-5 | LED | E4 approval | ECE R87 | 85122000900 |

| Environmental & Regulatory Information |
|---|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |

| | Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | |
|---------------------|---|----------------------|--|--|
| Product description | Candidate list substance 1 | CAS No. of substance | Safe use instruction | Declaration no. in SCIP database |
| LEDriving PX-5 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 24fd4b7d-c774-46f3- 9b44-7c1767b813ea |
| LEDriving PX-5 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 7a05b6d4-2aed- 41c9-afdf- 7da8dfd39471 |

Product family datasheet

Download Data

| | File |
|----------|--|
| Z | User instruction LED Daytime Running Light Kit LEDDRL301 (User Manual) |
| | User instruction LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual) |
| Z | User instruction GPRS_Safety symbols instructions |

Legal advice

ECE E4 approvalECE R87 approval

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















