

FOG BREAKER

Up to 200% more yellow light



Up to 200% more yellow light
Compared to standard lamps



Up to 60% more light
For better visibility and significantly
shorter reaction times compared to
standard halogen lamps



Up to 2,600 K
Better sight when driving in fog, rain,
snow and sandstorm weather



Better sight in fog, rain and snow

With up to 200% more yellow light and up to 60% more light compared to standard lamps, FOG BREAKER ensures better sight, even under the most challenging weather conditions like fog, rain, snow and sandstorm. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Product type (off-road vs. on-road)	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage
FOG BREAKER ≙ H1	Off-road ≙ H1	Halogen headlight lamp	62150FBR	68 W ¹⁾	12 V
FOG BREAKER ≙ H3	Off-road ≙ H3	Halogen headlight lamp	62151FBR	68 W ¹⁾	12 V
FOG BREAKER ≙ H4	Off-road ≙ H4	Halogen headlight lamp	62193FBR	75 / 68 W ¹⁾	12 V
FOG BREAKER ≙ H7	Off-road ≙ H7	Halogen headlight lamp	62210FBR	58 W ¹⁾	12 V
FOG BREAKER ≙ H8	Off-road ≙ H8	Halogen headlight lamp	64212FBR	43 W ¹⁾	12 V
FOG BREAKER ≙ H11	Off-road ≙ H11	Halogen headlight lamp	64211FBR	62 W ¹⁾	12 V
FOG BREAKER ≙ H16	Off-road ≙ H16	Halogen headlight lamp	62219FBR	22.5 W ¹⁾	12 V
FOG BREAKER ≙ HB3	Off-road ≙ HB3	Halogen headlight lamp	9005FBR	73 W ¹⁾	12 V
FOG BREAKER ≙ HB4	Off-road ≙ HB4	Halogen headlight lamp	9006FBR	62 W ¹⁾	12 V

Product description	Nominal wattage	Test voltage	Photometric Data		Physical Attributes & Dimensions
			Nominal luminous flux	Luminous flux tolerance	Diameter
FOG BREAKER ≙ H1	55 W	13.2 V	1500 lm	±15 %	8.5 mm
FOG BREAKER ≙ H3	55 W	13.2 V	1550 lm	±15 %	11.0 mm
FOG BREAKER ≙ H4	60/55 W	13.2 V	1700/1100 lm	±15 %	17.0 mm
FOG BREAKER ≙ H7	55 W	13.2 V	1750 lm	±15 %	12.0 mm
FOG BREAKER ≙ H8	35 W	13.2 V	1350 lm	±15 %	11.7 mm
FOG BREAKER ≙ H11	55 W	13.2 V	1750 lm	±15 %	12.0 mm
FOG BREAKER ≙ H16	19 W	13.2 V	500 lm	+10 %...15 %	9.5 mm
FOG BREAKER ≙ HB3	60 W	13.2 V	1700 lm	±12 %	12.0 mm
FOG BREAKER ≙ HB4	51 W	13.2 V	1100 lm	±15 %	12.0 mm

Product family datasheet

		Lifetime Data		Capabilities	Certificates & standards	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Product description	Diameter	Lifespan B3	Lifespan Tc	Technology	ECE category	Primary article identifier
FOG BREAKER ≙ H1	8.5 mm	400 hr	650 hr	HAL		4052899039681 4052899932210
FOG BREAKER ≙ H3	11.0 mm	400 hr	650 hr	HAL		4052899932227 4052899039704
FOG BREAKER ≙ H4	17.0 mm	250 / 400 hr ²⁾	500 / 900 hr ²⁾	HAL		4052899932234 4052899039735
FOG BREAKER ≙ H7	12.0 mm	330 hr	550 hr	HAL		4052899932203 4052899039766
FOG BREAKER ≙ H8	11.7 mm	400 hr	800 hr	HAL		4052899503298 4052899233959
FOG BREAKER ≙ H11	12.0 mm	350 hr	580 hr	HAL		4052899932241 4052899039780
FOG BREAKER ≙ H16	9.5 mm			HAL		4052899280922
FOG BREAKER ≙ HB3	12.0 mm	280 hr	550 hr	HAL		4052899047556 4052899932258 4052899047532
FOG BREAKER ≙ HB4	12.0 mm	860 hr	1720 hr	HAL		4052899047570 4052899047594 4052899932265

Product description	Candidate list substance 1	Declaration no. in SCIP database
FOG BREAKER ≙ H1	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H3	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H4	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H7	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H8	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H11	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H16	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ HB3	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ HB4	No declarable substances contained	No declarable substances contained

1) Maximum

2) Filament 1

Download Data

File	
	User instruction GPRS_Safety symbols instructions

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

