

LINEARlight FLEX Tunable White IP00

Linear LED modules for flexible and individualized lighting solutions



A termék jellemzői

- 24 V LED strips flexible and cuttable
- Up to 60,000 h L90/B10 with SDT technology, tested acc. to IEC 62717 on real LED strips
- Adjustable color temp. via Tunable White: 2200...3500 K, 2500...4000 K, 2700...5700 K CRI90
- Adjustable color temp. via Tunable White: 2200...3500 K, 2500...3500 K, 2700...6500 K CRI80
- CRI80, CRI90 options available
- Stable light flux over length: active constant current regulators (ICs), PWM safe
- Embedded automatic quick protection against accidental miswiring up to 25 V
- Fully PWM dimmable from zero up to 2.5 kHz, audible noise free, suitable for quite places
- Designed, engineered and manufactured and tested in Italy (ISO9001, ISO 17025, ACCREDIA, VDE)

A termék előnyei

- Color uniformity better than 3 SDCM on the entire LED strip and between strips
- LED lifetime acc.to IES LM-80 and IES TM-21 standards, and also internal OSRAM LAB tests
- Excellent robustness: single reel manufacturing technology (no solder joints on strip)
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
- Extraordinary design and high quality materials
- Pre-soldered wires

Alkalmazási területek

- Cove lighting
- Shop lighting
- Offices



Termékcsalád adatlap

Műszaki adatok

Termékmegnevezés	Elektromos adatok						Fotometriai adatok
	Névleges feszültség	Áram típusa	Névleges teljesítmény / m	Névleges feszültség	Bemeneti feszültségtartomány	Accidental reverse input voltage protection up to	Fényszín LED
LF3400TW-G5 -927.965-03 L1	240 V	DC	30.9 W	9270 W	23...25 V	25 V	Dynamic White
LF3400TW-G5 -927.957-03 L1	240 V	DC	30.2 W	9070 W	23...25 V	25 V	Dynamic White
LF3400TW-G5 -925.940-03 L1	240 V	DC	32.4 W	9730 W	23...25 V	25 V	Dynamic White
LF3400TW-G5 -922.935-03 L1	240 V	DC	34.7 W	10400 W	23...25 V	25 V	Dynamic White
LF1100TW-G5 -927.965-09 L2	240 V	DC	9,8 W	8840 W	23...25 V	25 V	Dynamic White
LF1100TW-G5 -927.957-09 L2	240 V	DC	9,8 W	8840 W	23...25 V	25 V	Dynamic White
LF1100TW-G5 -925.940-09 L2	240 V	DC	10,4 W	9360 W	23...25 V	25 V	Dynamic White
LF1100TW-G5 -922.935-09 L2	240 V	DC	10,9 W	9850 W	23...25 V	25 V	Dynamic White

Termékmegnevezés	Színvisszaadási index	Fényáram / m	Luminous efficacy	Színegyeztetés szórása	Fényszín (megnevezés)	Méreték és súly
						Hosszúság
LF3400TW-G5 -927.965-03 L1	90	3400 lm	110 lm/W	≤3 sdcm	2700...6500 K	30000 mm
LF3400TW-G5 -927.957-03 L1	90	3400 lm	113 lm/W	≤3 sdcm	2700...5700 K	30000 mm
LF3400TW-G5 -925.940-03 L1	90	3400 lm	105 lm/W	≤3 sdcm	2500...4000 K	30000 mm
LF3400TW-G5 -922.935-03 L1	90	3400 lm	98 lm/W	≤3 sdcm		30000 mm
LF1100TW-G5 -927.965-09 L2	90	1156 lm	118 lm/W	≤3 sdcm	2700...6500 K	90000 mm
LF1100TW-G5 -927.957-09 L2	90	1156 lm	118 lm/W	≤3 sdcm	2700...5700 K	90000 mm
LF1100TW-G5 -925.940-09 L2	90	1156 lm	111 lm/W	≤3 sdcm	2500...4000 K	90000 mm
LF1100TW-G5 -922.935-09 L2	90	1111 lm	102 lm/W	≤3 sdcm		90000 mm

Termékmegnevezés	Vezetékhossz [calc.]	Termék súlya	Hőmérséklet és működési feltételek		További termékadatok
			Hőmérséklet-tartomány működéskor	Hőmérséklet-tartomány tároláskor	ID of contained light source [AGGR]
LF3400TW-G5 -927.965-03 L1	5000	3500 g	-20...+85 °C ¹⁾	-40...+85 °C	LS_TRV_286287
LF3400TW-G5 -927.957-03 L1	5000	3500 g	-20...+85 °C ¹⁾	-40...85 °C	LS_TRV_286066
LF3400TW-G5 -925.940-03 L1	5000	3500 g	-20...+85 °C ¹⁾	-40...85 °C	LS_TRV_286065
LF3400TW-G5 -922.935-03 L1	5000	3500 g	-20...+85 °C ¹⁾	-40...85 °C	LS_TRV_286064
LF1100TW-G5 -927.965-09 L2	5000	10400 g	-20...+85 °C ¹⁾	-40...+85 °C	LS_TRV_286286

Termékcsalád adatlap

Termékmegnevezés	Vezetékhossz [calc.]	Termék súlya	Hőmérséklet és működési feltételek		További termékadatok
			Hőmérséklet-tartomány működéskor	Hőmérséklet-tartomány tároláskor	ID of contained light source [AGGR]
LF1100TW-G5 -927.957-09 L2	5000	10400 g	-20...+85 °C ¹⁾	-40...85 °C	LS_TRV_286063
LF1100TW-G5 -925.940-09 L2	5000	10400 g	-20...+85 °C ¹⁾	-40...85 °C	LS_TRV_286062
LF1100TW-G5 -922.935-09 L2	5000	10400 g	-20...+85 °C ¹⁾	-40...85 °C	LS_TRV_286061

Termékmegnevezés	Utód EAN	Képességek	Tanúsítványok és szabványok	
		Dimmelhető	Energy efficiency class of the contained light source	Szabványok
LF3400TW-G5 -927.965-03 L1		Yes	F	
LF3400TW-G5 -927.957-03 L1	4062172032605, 4062172032629		F	CE/ENEC/EAC
LF3400TW-G5 -925.940-03 L1			F	CE/ENEC/EAC
LF3400TW-G5 -922.935-03 L1	4052899563339		F	CE/ENEC/EAC
LF1100TW-G5 -927.965-09 L2		Yes	F	
LF1100TW-G5 -927.957-09 L2	4062172032667, 4062172032643		F	CE/ENEC/EAC
LF1100TW-G5 -925.940-09 L2			F	CE/ENEC/EAC
LF1100TW-G5 -922.935-09 L2			F	CE/ENEC/EAC

Termékmegnevezés	Logisztikai adatok	Környezetvédelmi információk Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)		
	Commodity code	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
LF3400TW-G5 -927.965-03 L1	85395100000	26-05-2023	4062172263719	Lead
LF3400TW-G5 -927.957-03 L1	85395100000	09-06-2023	4062172189354	Lead
LF3400TW-G5 -925.940-03 L1	85395100000	09-06-2023	4062172189330	Lead
LF3400TW-G5 -922.935-03 L1	85395100000	09-06-2023	4062172189316	Lead
LF1100TW-G5 -927.965-09 L2	85395100000	19-05-2023	4062172263696	Lead
LF1100TW-G5 -927.957-09 L2	85395100000	09-06-2023	4062172189293	Lead
LF1100TW-G5 -925.940-09 L2	85395100000	09-06-2023	4062172189279	Lead
LF1100TW-G5 -922.935-09 L2	85395100000	09-06-2023	4062172189255	Lead


Termékmegnevezés	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LF3400TW-G5 -927.965-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3d44363c-fe56-4bbd-97a6-860743cbd9c5

Termékcsalád adatlap


Termékmegnevezés	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LF3400TW-G5 -927.957-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6dfc036b-ceb0-4e6b-9095-48384a422e91
LF3400TW-G5 -925.940-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3b0dc5f1-547b-441b-bd5e-9960b615b212
LF3400TW-G5 -922.935-03 L1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9c2d531d-dbbb-487a-b4d4-50328cc7dc74
LF1100TW-G5 -927.965-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d751d4ed-f883-4c1c-834c-4e9ef2896222
LF1100TW-G5 -927.957-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	1e4aef2d-5fd2-4940-9779-142c985ead14
LF1100TW-G5 -925.940-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	39d314f8-b6f9-41f5-acad-622e0887ed2a
LF1100TW-G5 -922.935-09 L2	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	103ac832-f72b-4c34-b09f-89e3b075d569

1) Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

Termékcsalád adatlap



LINEARlight Flex Tunable White IP00 L1 drawing



LINEARlight Flex Tunable White IP00 L2

Equipment / Accessories

- Simplified connection with optional matching CONNECTsystem
- Perfectly matched with OTi DALI 50/80 4CH DT6/8 and OTi DALI 160 2CH DT6/8
- Perfectly matched with OTi BLE 80/220-240/24 4CH

Használati tanácsok

További részletes alkalmazási információkat és grafikákat a termék adatlapján talál.

Adatlap szöveg

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Sales and Technical Support

Sales and Technical Support www.osram.com

Download Data

File	
	User instruction LINEARlight FLEX, Tunable White
	Product Datasheet LINEARlight Flex Tunable White CRI90 Specification Sheet (EN)

Termékcsalád adatlap

	Brochures Light is freedom of design (EN)
	Certificates VDE ENEC CERTIFICATE 40052516 160823
	Certificates LF(P) TW G5 CB 180121
	Declarations of conformity LR FLEX TW2 CE 4249165 02 020823
	Eulumdat LF3400TW-G5-927.957-03 L1 LTD 130421
	IES data LF3400TW-G5-927.957-03 L1 IES 130421
	Eulumdat LF3400TW-G5-925.940-03 L1 LTD 130421
	IES data LF3400TW-G5-925.940-03 L1 IES 130421
	Eulumdat LF3400TW-G5-922.935-03 L1 LTD 130421
	IES data LF3400TW-G5-922.935-03 L1 IES 130421
	Eulumdat LF1100TW-G5-927.957-09 L2 LTD 130421
	IES data LF1100TW-G5-927.957-09 L2 IES 130421
	Eulumdat LF1100TW-G5-925.940-09 L2 LTD 130421
	IES data LF1100TW-G5-925.940-09 L2 IES 130421
	Eulumdat LF1100TW-G5-922.935-09 L2 LTD 130421
	IES data LF1100TW-G5-922.935-09 L2 IES 130421

Termékcsalád adatlap

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4062172263719	LF3400TW-G5 -927.965-03 L1	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1213.00 g
4062172189354	LF3400TW-G5 -927.957-03 L1	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1213.00 g
4062172189330	LF3400TW-G5 -925.940-03 L1	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1213.00 g
4062172189316	LF3400TW-G5 -922.935-03 L1	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1213.00 g
4062172263696	LF1100TW-G5 -927.965-09 L2	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1765.00 g
4062172189293	LF1100TW-G5 -927.957-09 L2	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1765.00 g
4062172189279	LF1100TW-G5 -925.940-09 L2	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1765.00 g
4062172189255	LF1100TW-G5 -922.935-09 L2	Karton 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1765.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Opcionális tartozékok

Termékcsalád adatlap

Termékmegnevezés	Tartozékok neve	Tartozékok kódja
LF3400TW-G5 -927.965-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF3400TW-G5 -927.965-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF3400TW-G5 -927.965-03 L1	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF3400TW-G5 -927.965-03 L1	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF3400TW-G5 -927.965-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF3400TW-G5 -927.965-03 L1	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF3400TW-G5 -927.965-03 L1	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3400TW-G5 -927.957-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF3400TW-G5 -927.957-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF3400TW-G5 -927.957-03 L1	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF3400TW-G5 -927.957-03 L1	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF3400TW-G5 -927.957-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF3400TW-G5 -927.957-03 L1	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF3400TW-G5 -927.957-03 L1	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3400TW-G5 -925.940-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF3400TW-G5 -925.940-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF3400TW-G5 -925.940-03 L1	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF3400TW-G5 -925.940-03 L1	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF3400TW-G5 -925.940-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF3400TW-G5 -925.940-03 L1	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF3400TW-G5 -925.940-03 L1	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3400TW-G5 -922.935-03 L1	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF3400TW-G5 -922.935-03 L1	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF3400TW-G5 -922.935-03 L1	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF3400TW-G5 -922.935-03 L1	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF3400TW-G5 -922.935-03 L1	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF3400TW-G5 -922.935-03 L1	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF3400TW-G5 -922.935-03 L1	FX -SC08-G2-CT4PJ	▶ 4052899464858

Termékcsalád adatlap

LF1100TW-G5 -927.965-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF1100TW-G5 -927.965-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF1100TW-G5 -927.965-09 L2	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF1100TW-G5 -927.965-09 L2	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF1100TW-G5 -927.965-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF1100TW-G5 -927.965-09 L2	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF1100TW-G5 -927.965-09 L2	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF1100TW-G5 -927.957-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF1100TW-G5 -927.957-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF1100TW-G5 -927.957-09 L2	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF1100TW-G5 -927.957-09 L2	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF1100TW-G5 -927.957-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF1100TW-G5 -927.957-09 L2	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF1100TW-G5 -927.957-09 L2	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF1100TW-G5 -925.940-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF1100TW-G5 -925.940-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF1100TW-G5 -925.940-09 L2	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF1100TW-G5 -925.940-09 L2	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF1100TW-G5 -925.940-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF1100TW-G5 -925.940-09 L2	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF1100TW-G5 -925.940-09 L2	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF1100TW-G5 -922.935-09 L2	CORNER-FLEX -4P-003 KIT 10PCS	▶ 4062172179638
LF1100TW-G5 -922.935-09 L2	CORNER-FLEX -4P-015 KIT 10PCS	▶ 4062172179676
LF1100TW-G5 -922.935-09 L2	CONN-FLEX -3P-050 KIT 10PCS	▶ 4062172179690
LF1100TW-G5 -922.935-09 L2	CONN-FLEX -3P-200 KIT 10PCS	▶ 4062172179720
LF1100TW-G5 -922.935-09 L2	LTS-SLIMTRACK -2000 KIT 5 PCS	▶ 4062172207300
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LF1100TW-G5 -922.935-09 L2	FX-QMS-G1 -TU16H12-300	▶ 4052899448964
LF1100TW-G5 -922.935-09 L2	FX -SC08-G2-CT4PJ	▶ 4052899464858

Lemondás

A változtatás jogát fenntartjuk. Hibák és mulasztások kizárva. Mindig győződjön meg arról, hogy a legújabb kiadást használja.