

## DALI ACU BT

DALI ACU BT | Control units for light management systems



### A termék jellemzői

- Compact light control with DALI interface
- Up to 32 DALI luminaires connectable
- Supports up to 4 OSRAM DALI sensors and pushbutton couplers
- Daylight-dependent regulation and presence-dependent control of light
- Separate pushbutton input to operate via standard pushbutton
- Supports DALI DT8 Tunable White driver
- Outputs with electrical reversible overtemperature, short-circuit, overload protection
- Length of the DALI control cable: up to 300 m
- Suitable for flush box mounting

### A termék előnyei

- Control the light via Smartphone
- Adjustment of all settings via smartphone
- Plug and Play: Basic features usable without App
- Simplified startup thanks to predefined operation modes
- Adjustable Offset for different groups
- Easy Scene creation via App
- Selected DALI parameters changeable via APP

### Alkalmazási területek

- Offices
- Conference rooms
- Training rooms
- Classrooms
- Corridors
- Shop lighting


## Termék adatlap

### Műszaki adatok

#### Elektromos adatok

Névleges feszültség	220...240 V
Hálózati frekvencia [calc.]	50 Hz/60 Hz
System wattage	3.00 W

#### Méretetek és súly



Hosszúság	49.0 mm
Szélesség	48.0 mm
Magasság	22.0 mm
Termék súlya	40.00 g

#### Szín és anyag

Termék színe	Világos szürke
--------------	----------------

#### Hőmérséklet és működési feltételek

Környezeti hőmérséklet tartomány	-20...+60 °C
----------------------------------	--------------

#### Képességek

Dimmelhető	No
Dimmelő interfész	DALI
Vezérlő kimenetek száma	1
Adó hatótávolsága	15 m
Installáció típusa	Luminaire integration/Kötődobozba integrált

#### Tanúsítványok és szabványok

Védettség típusa	IP20
Érintésvédelmi osztály	II

## Termék adatlap

Jóváhagyási jelek	CE
-------------------	----





### Logisztikai adatok

Commodity code	853710989900
----------------	--------------

### Környezetvédelmi információk

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	26-05-2023
Primary Article Identifier	4052899544819
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	dc2f44f4-d115-43f7-beb1-965da995f32f

### Download Data

File
 User instruction DALI ACU BT Control
 User instruction DALI ACU BT Control
 Brochures Light is easy to use - Plug-and-play app control solutions... (EN)
 Certificates DALI Zigbee DALI VDE 40047700 080422

### Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4052899544819	DALI ACU BT	Karton 60	344 mm x 254 mm x 278 mm	24.29 dm <sup>3</sup>	3861.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Opcionális tartozékok

## Termék adatlap

Termékmegnevezés	Tartozékok neve	Tartozékok kódja
DALI ACU BT	DALI LS/PD LI	▶ 4052899043954
DALI ACU BT	LS/PD AP KIT	▶ 4052899173385
DALI ACU BT	DALI LS/PD CI	▶ 4052899930292

---

### Lemondás

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.