

Termék adatlap

P MR16 DIM 800 W/930 GU5.3

PARATHOM MR16 DIM | Dimmable low-voltage LED reflector lamps MR16 with retrofit pin base



- Shops and exhibition rooms Domestic applications
Commercial applications Accent lighting Outdoor use in
outdoor luminaires only (minimum IP65)

- Quick, simple and safe replacement without rewiring Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Low maintenance costs thanks to long lifetime No UV and near-IR radiation in the light beam Stepless dimming Very high dimmer compatibility, see also "www.ledvance.com/dim" Compatible with many common conventional and electronic control gears (see also "compatibility list") Instant 100 % light, no warm-up time



Műszaki adatok

Elektromos adatok

ZLDV_Claimed equiv. conventional lamp power [AGGR]	50 W
ZLDV_Operating frequency [AGGR]	50/60 Hz
ZLDV_Nominal current [AGGR]	720 mA


Fotometriai adatok

ZLDV_Luminous intensity [AGGR]	1000 cd
ZLDV_Light color (designation) [AGGR]	Warm White
ZLDV_Nominal useful luminous flux 90° [AGGR]	561 lm
ZLDV_Rated peak intensity [AGGR]	1000 cd
ZLDV_Luminous flux [AGGR]	561 lm

Fénytechnikai adatok

ZLDV_Beam angle [AGGR]	36 °
ZLDV_Rated beam angle (half peak value) [AGGR]	36.00 °

Méretetek és súly



ZLDV_Overall length [AGGR]	46.00 mm
ZLDV_Product weight [AGGR]	43.00 g
ZLDV_Maximum diameter [AGGR]	50 mm

Hőmérséklet és működési feltételek

ZLDV_Ambient temperature range [AGGR]	-20...+40 °C
---------------------------------------	--------------

Élettartam

ZLDV_Lumen maintenance at end of service life [AGGR]	0.7
--	-----

További termékadatok

ZLDV_Mercury content [AGGR]	0.0 mg
ZLDV_Mercury-free [AGGR]	Yes
Ártalmatlanítás WEEE szerint	Yes
Utód EAN	4058075609297
ZLDV_Product remark [AGGR]	All technical parameters apply to the entire lamp Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Utód EAN	4058075095106, 4058075449442

Tanúsítványok és szabványok

ZLDV_Energy efficiency class [AGGR]	G
ZLDV_Energy consumption [AGGR]	9.00 kWh/1000h

Környezetvédelmi információk

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075449442 4058075609297
Declaration No. in SCIP database	In work

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4058075609297	P MR16 DIM 800 W/930 GU5.3	Karton 10 Pieces Folding Box	255 mm x 107 mm x 72 mm	1.96 dm ³	553.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Lemondás

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany