

Termékcsalád adatlap

OSRAM DULUX S LED EM

LED replacement for short CFLni, with 2-pin G23 base for CCG and AC mains operation



- Supermarkets and department stores Walkways and corridors Hotels, restaurants

- Quick, simple and safe replacement without rewiring Low energy consumption Easy relamping thanks to compact design Operation directly on 230 V AC mains possible



Műszaki adatok


Termékmegnevezés	Elektromos adatok			Fotometriai adatok	Fénytechnikai adatok	Méretek és súly	
	ZLDV_Operating frequency [AGGR]	ZLDV_Nominal current [AGGR]	ZLDV_Claimed equiv. conventional lamp power [AGGR]	ZLDV_Light color (designation) [AGGR]	ZLDV_Beam angle [AGGR]	ZLDV_Overall length [AGGR]	ZLDV_Product weight [AGGR]
DULUX S LED EM 450 W/830 G23 ¹⁾	50/60 Hz	21 mA	9 W	Warm White	140 °	165.00 mm	39.00 g
DULUX S LED EM 450 W/840 G23 ¹⁾	50/60 Hz	21 mA	9 W	Cool White	140 °	165.00 mm	39.00 g

Termékmegnevezés	Hőmérséklet és működési feltételek	Élettartam	Tanúsítványok és szabványok		Környezetvédelmi információk Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	ZLDV_Ambient temperature range [AGGR]	ZLDV_Lumen maintenance at end of service life [AGGR]	ZLDV_Energy efficiency class [AGGR]	ZLDV_Energy consumption [AGGR]	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
DULUX S LED EM 450 W/830 G23 ¹⁾	-20...+50 °C	0.7	F	5.00 kWh/1000h	18-04-2022	4058075557994	In work
DULUX S LED EM 450 W/840 G23 ¹⁾	-20...+50 °C	0.7	E	5.00 kWh/1000h	18-04-2022	4058075558045	In work

Termékmegnevezés	További termékadatok
	Utód EAN
DULUX S LED EM 450 W/830 G23 ¹⁾	
DULUX S LED EM 450 W/840 G23 ¹⁾	4058075135307

¹⁾ All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Termékcsalád adatlap



DULUX S LED EM 450 W/830 G23,
DULUX S LED EM 450 W/840 G23

Használati tanácsok

További részletes alkalmazási információkat és grafikákat a termék adatlapján talál.

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Termékcsalád adatlap

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4058075557994	DULUX S LED EM 450 W/830 G23	Karton 10	114 mm x 79 mm x 182 mm	1.64 dm ³	712.00 g
4058075558045	DULUX S LED EM 450 W/840 G23	Karton 10	114 mm x 79 mm x 182 mm	1.64 dm ³	712.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Lemondás

A változtatás jogát fenntartjuk. Hibák és mulasztások kizárva. Mindig győződjön meg arról, hogy a legújabb kiadást használja.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany