

BA-RGBW-PL G2

BackLED RGBW Plus G2 | LED modules for light advertising and backlighting



A termék jellemzői

- Connected with flexible cables
- Special robust encapsulation
- CE marked
- Dimmable by pulse width modulation (PWM)

A termék előnyei

- Simple fixing with M3 screws
- Broad color mixing palette (in connection with light management systems)
- Uniform backlighting of large surfaces thanks to extremely wide angle optics
- Simple connection with open cable ends
- 5 year guarantee



Termék adatlap

Alkalmazási területek

- Special-purpose and decorative lighting applications
- Dynamic color backlighting
- Dynamic mood lighting
- Spas
- Shops
- Restaurants
- Trade fair lighting
- Permanent outdoor use in enclosed light boxes or channel letters

Termék adatlap

Műszaki adatok

Elektromos adatok

Névleges feszültség	24.0 V
Névleges teljesítmény LED modulonként	2.84 W
Accidental reverse input voltage protection up to	24 V
Bemeneti feszültségtartomány	23...25 V
Áram típusa	DC
Névleges teljesítmény lánconként	42.60 W


Fotometriai adatok

Fényszín (megnevezés)	RGBW
Fényszín LED	RGB, white
Fényáram / lánc	2310 lm
Luminous efficacy	54 lm/W
Színegyeztetés szórása	≤5 sdcn
Fényáram / LED modul	154 lm
Luminous flux per LED module at Ta 25 °C	142 lm
Luminous flux per LED module at Tc 25 °C	154 lm
Luminous flux per chain at Ta 25 °C	2125 lm
Luminous flux per chain at Tc 25 °C	2310 lm

LED modul információ

LED-ek száma / modul	8
LED modulok száma a láncban	15
LED modulok legkisebb működtethető száma	3

Méretetek és súly



Termék súlya	900.00 g
--------------	----------

Termék adatlap

Hosszúság	129.0 mm
Szélesség	35.0 mm
Magasság	15.5 mm

Hőmérséklet és működési feltételek

Hőmérséklet-tartomány működéskor	-25...75 °C
Hőmérséklet-tartomány tároláskor	-25...65 °C

Képességek


Dimmelési tartomány	5...100 %
---------------------	-----------

Tanúsítványok és szabványok

Védettség típusa	IP66
Szabványok	CE
Jóváhagyási jelek	CE

Logisztikai adatok

Commodity code	940540399000
----------------	--------------



484525_5 Year Osram Guarante
(GB)

Equipment / Accessories




- Several types of OPTOTRONIC 24 V power supplies available
- BoxLED mounting profile BX-MP

Termék adatlap

Adatlap szöveg

- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- Installation by qualified electrician only.
- Please see the relevant application guides and instructions sheets for more detailed safety and mounting information. Additional information is available on request.
- Complies with IEC/EN 61547
- Complies with IEC/EN 61000-3-2
- Complies with EN 55015, CISPR 15
- Complies with IEC/EN 61347-1
- Complies with IEC/EN 61347-2-13
- LED modules are dimmable by means of PWM (pulse width modulation). It is recommended using the following OSRAM control gears: OPTOTRONIC OT DIM or OPTOTRONIC 24 V power supplies with integrated 1...10 V dimming interface.
- Parallel connection is mandatory for safe electrical operation. Serial connection of LED modules is strongly discouraged. Unbalanced voltage drop in serial connection can cause hazardous overload and damage the LED module.
- Electrical contact is achieved with the contact cables or the terminals of the module. Please refer to the technical data for maximum number of LED modules that can be operated on one control gear.
- In order to operate OSRAM LED modules safely, it is absolutely necessary to operate them with an electronically stabilized power supply that protects against short circuits, overload and overheating.
- In case other power supplies than OSRAM OPTOTRONIC are used, compliance to the necessary operating parameters (voltage, current, power) has to be ensured.
- Pay attention to polarity! Wrong polarity can cause destruction or malfunction of the module.
- Conducting paths on the circuit board must not be damaged or destroyed during installation.
- The LED module itself and all its components must not be stressed mechanically.
- Operation in or under water is prohibited.
- To avoid mechanical damage, the LED modules have to be attached securely to the intended mounting surface. It is recommended to avoid heavy vibration.
- In case that the LED module is equipped with a pre-mounted double-sided adhesive tape, OSRAM assumes no liability and provides no guarantee for a permanent adherence of the modules to the surface. OSRAM recommends fixation of the modules by means of suitable screws.
- Complies with IEC 61347-1 cl. 18.3, cl. 18.4, IEC 60695-2-10, IEC 60695-11-5, IEC 60695-11-10 (classification V-0)
- All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the specified typical values for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.
- Module contains no PVC material.
- To ensure uniform illumination, a reflective matt white surface is generally recommended for all internal frame walls and back panels of light boxes.
- The module may cause noises during dimming. If a dimming operation is required, it is recommended to check the dimming operation for noises before final installation.

Download Data

File	
	User instruction UI BackLED TW and RGBW Plus G2
	Declarations of conformity 727530_EC BackLED PLUS
	Declarations of conformity 727532_Manufacturer's Declaration BackLED PLUS

Termék adatlap

	CAD data 728616_CAD_BackLED RGBW Plus G2_dwg
	CAD data 728617_CAD_BackLED RGBW Plus G2_isg
	CAD data 3-dim 728618_CAD_BackLED RGBW Plus G2_step
	CAD data PDF 728615_CAD BackLED RGBW Plus G2_pdf
	Eulumdat 728621_BackLED RBGW Plus G2 BA-RGBW-PL_Blue_4052899452930
	Eulumdat 728622_BackLED RBGW Plus G2 BA-RGBW-PL_Green_4052899452930
	Eulumdat 728623_BackLED RBGW Plus G2 BA-RGBW-PL_RGBW_4052899452930
	Eulumdat 728624_BackLED RBGW Plus G2 BA-RGBW-PL_Red_4052899452930
	Eulumdat 728625_BackLED RBGW Plus G2 BA-RGBW-PL_White_4052899452930
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2
	IES data IES_BackLED RBGW Plus G2

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4062172030168	BA-RGBW-PL G2	Karton 5	473 mm x 328 mm x 292 mm	45.30 dm ³	7277.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the multi-level guarantee and the terms and conditions of the guarantee visit

▶ www.osram.com/system-guarantee

Termék adatlap

Lemondás

A változtatás jogát fenntartjuk. Hibák és mulasztások kizárva. Mindig győződjön meg arról, hogy a legújabb kiadást használja.