

PrevaLED Linear TW G2

Linear Light Engines



A termék jellemzői

- Module efficacy: up to 170 lm/W with 2,700K
- Module efficacy: up to 190 lm/W with 6,500K
- Available module length: 62 mm, 280 mm, 560 mm
- Available with luminous flux: 245 lm, 1,100 lm and 2,200 lm
- Initial color consistency: ≤ 3 SDCM
- Average lifetime (L80 B50): up to 70,000 h (temperature at $T_c = 55^\circ\text{C}$)

A termék előnyei

- SELV or non-isolated LED Module with perfect match to Optotronic TW driver

Alkalmazási területek

- Offices
- Education

Termékcsalád adatlap

Használati tanácsok

További részletes alkalmazási információkat és grafikákat a termék adatlapján talál.

Sales and Technical Support

Sales and Technical Support www.osram.com

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Lemondás

A változtatás jogát fenntartjuk. Hibák és mulasztások kizárva. Mindig győződjön meg arról, hogy a legújabb kiadást használja.