### Product family datasheet

# LEDriving SL P21W YELLOW

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Amber



**Replaces conventional P21W lamps** Easy upgrade to LED technology with

plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product family datasheet

# Technical data

Product information			General Product Information		Electrical Data			
Product description	Product type (off- road vs. on-road)	Application (Categ and Product specif	plication (Category Global d Product specific) referen		Power input	Nominal voltage		
LEDriving SL ≙ P21W	Off-road ≙ P21W	Mainly used for signal/ indicator applications	7506	DYP	1.8 W	12 V		
				Photomet	ric Data	Physical A Dimension	attributes &	
Product description	Nominal watt	age Power input toleranc e	Test voltage		Nominal luminous flux		Lamp base	
LEDriving SL $\triangleq$ P21W	1 W	±25 %	13.5 V	50 lm		BA15s		
						Lifetime D	Data	
Product description	Length	Diamete	r	Diameter		Lifespan B3	Lifespan Tc	
LEDriving SL $\doteq$ P21W	52.5 mm	25.0 mm	1	25.0 mm		1500 hr	4000 hr	
	Capabilities	Capabilities Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/ (REACh)						
Product description	Technology	Primary article identifier		ididate list stance 1	CAS No 1	CAS No. of substance 1		
LEDriving SL $\triangleq$ P21W	LED <sup>1)</sup>	4062172152228	l Lea	Lead 7439-9		92-1		

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving SL $\doteq$ P21W	The identification of	558ba419-9f08-
	the Candidate List	4a0e-b0ad-
	substance is	fa29ec684e7c
	sufficient to allow	f893b2c4-9d2c-4d79-
	safe use of the	ac1d-e1942146ed73
	article.	

 $^{1)}$  Light-emitting diode lamp

\_\_\_\_

# Product family datasheet

#### Download Data

File
User instruction GPRS_Safety symbols instructions
Brochures LEDriving Retrofits - Exchange overview (EN)

#### Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.