OSRAM

LEDriving SL P27/7W RED

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Red



Replaces conventional P27/7W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P27/7W

LEDriving SL P27/7W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Electrica | Electrical Data | | | | | |
|---------------------|-------------|-----------------|-----------------|---------------------------------|-----------------|------------------------------|--|
| Product description | Power input | Nominal voltage | Nominal wattage | Power input toleranc e | Test voltage | Nominal luminou s flux | |
| LEDriving SL | 1.8 W | 12 V | 1 W | ±25 % | 13.5 V | 60/10 Im | |

| | I | | | | | |
|-----------------------|----------------------------------|----------------|--|----------------------------|--------|--|
| | Physical Attributes & Dimensions | | | | | |
| Product description | Lamp base | Length | Diameter | Dia | ameter | |
| LEDriving SL ≙ P27/7W | W2.5x16q | 49.0 mm | 25.7 mm | 25 | 5.7 mm | |
| | Lifetime Data | | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | n | |
| Product description | Lifespan B3 | Lifespan Tc | Primary article identifier | Candidate list substance 1 | | |
| LEDriving SL ≜ P27/7W | 1500 hr | 4000 hr | 4062172151689 4062172401777 | Lead | | |

| Product description | CAS No. of substance | Safe use instruction | Declaration no. in SCIP database |
|-----------------------|----------------------|---|--|
| LEDriving SL ≙ P27/7W | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | a5c512b0-7fa2- 4907-bc1f- 816fe7f2d8ed |

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.