

LEDDriving SL P13W

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P13W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P13W

LEDDriving SL P13W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P13W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Electrical Data | | | | | Photometric Data |
|---------------------------------|-----------------|-----------------|-----------------|-----------------------|--------------|-----------------------|
| | Power input | Nominal voltage | Nominal wattage | Power input tolerance | Test voltage | Nominal luminous flux |
| LEDDriving SL \triangleq P13W | 1.90 W | 12 V | 1 W | $\pm 10\%$ | 13.5 V | 130 lm |

| Product description | Physical Attributes & Dimensions | | | |
|---------------------------------|----------------------------------|---------|----------|----------|
| | Lamp base | Length | Diameter | Diameter |
| LEDDriving SL \triangleq P13W | PG18.5d-1 | 48.3 mm | 23.0 mm | 23.0 mm |

| Product description | Lifetime Data | | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---------------------------------|---------------|-------------|---|----------------------------|
| | Lifespan B3 | Lifespan Tc | Primary article identifier | Candidate list substance 1 |
| LEDDriving SL \triangleq P13W | 1500 hr | 4000 hr | 4062172401432 4062172150279 | Lead |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|---------------------------------|------------------------|--|---|
| LEDDriving SL \triangleq P13W | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 5d297eba-e23a-4652-864d-445415f98c63 86a80c4c-80ba-4d88-b8fd-60cafbfef775 |

Download Data

| File | |
|---|---|
|  | User instruction GPRS_Safety symbols instructions |
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.