OSRAM

Lightbar VX250-CB



ECE certified - ECE R112

The necessary tests and approvals were carried out and an ECE type approval was granted 2) ECE reference number: 12.5



Combo Beam

Designed for both: far-field and near-field illumination. For widespread illumination in the near field and spot illumination in the far field.



Light beam up to 170 m length

See and be seen with OSRAM



On-road & Off-road

Versatile applicable and flexible in use.On-road & off-road, in terrain, at work and in the spare time.



Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Lightbar VX250-CB. With its 24 powerful, high-performance long-life LEDs, the OSRAM LEDriving Lightbar VX250-CB has a range of up to 170 meter and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Lightbar VX250-CB with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 2100 lumens of luminosity scores with highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road. Whether on-road or off-road - The OSRAM LEDriving Lightbar VX250-CB impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Lightbar VX250-CB has been tested and validated with the IP-Protection Class IP67 in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat,

cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the LED Lightbar and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Lightbar VX250-CB is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECE-certified LED driving lights²⁾.

ECE reference number: 12.5

The OSRAM LEDriving Lightbar VX250-CB can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, offroad vehicles and quads²⁾.

The OSRAM LEDriving VX250-CB is versatile applicable and flexible in use.

2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

Technical data

	Product inf	Product information		General Product Information		trical Data		
Product description		Application (Category and Product specific)		Global order reference		ninal voltage	e Nominal wattage	
Lightbar VX250-CB ¹⁾	Additional application	high beam LEDDL117-CB		12/24 V		30 W		
		Photomet	ric Data	LED modu		Lifetime Data	Capabilities	
Product description	Test voltage	Nominal li flux	uminous	Number of LEDs per module	f	Lifespan Tc	Technology	
Lightbar VX250-CB ¹⁾	13.2 V	2100 lm		24		5000 hr	LED ²⁾	
	Certificates standards	Certificates & standards		Logistical data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		

ECE reference

number

12.5

Product description	Safe use instruction	Declaration no. in SCIP database
Lightbar VX250-CB ¹⁾	The identification of	227aeefc-65df-4d15-
	the Candidate List	ad5d-8f5c57c37152
	substance is	e6c264b6-4345-
	sufficient to allow	4117-be5c-
	safe use of the	ae5ad9b9ac00
	article.	234134cf-2af6-45fa-
		8503-5a28c5f9a975
		c994f8c0-bee0-4e9c-
		b29d-5113876a4982

Commodity code

85122000900

Candidate list

substance 1

Lead

CAS No. of substance

7439-92-1

Product description

Lightbar VX250-CB ¹⁾

¹⁾ Beam Pattern: Combo

 $^{^{2)}}$ Light-emitting diode application

Download Data

	File
太	User instruction LEDriving Lightbar VX250-CB DR
X	User instruction GPRS_Safety symbols instructions
D	Movie application LEDriving D and W Image Video Bringing light to life (EN)
	Movie application Working and Driving Lights Amarok Winter
	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
O	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
D	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
	ref_pim_amsp_product360degreeimages LEDriving Lightbar VX250-CB LEDDL117-CB

Legal advice

Legal advice:

The installation of the OSRAM LEDriving Lightbar VX250-CB is fully ECE compliant and therefore registration free. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product.

- 1) Precise terms and conditions at: www.osram.com/am-guarantee
- 2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.Refer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.