


PL-BRICK HP-Z2 1900 722 2X4

PrevaLED BRICK HP Z2 | LED modules for industry and outdoor applications

A termék jellemzői

- Module efficacy: up to 186 lm/W
- Available with color temperature: 2,200 K, 2,700 K, 3,000 K and 4000 K



Alkalmazási területek

- Street lighting
- Industry
- Area lighting



Műszaki adatok

Elektromos adatok

Névleges áram	07 A
Áram típusa	DC
Névleges feszültség	230 V
On-mode power [AGGR]	16.00 W
Energy consumption in on-mode [AGGR]	16.0 kWh/1000h

Fotometriai adatok

Luminous efficacy	133 lm/W
Színvisszaadási index	70
Correlated color temperature CCT [AGGR]	2200 K
Colour consistency (McAdam ellipses) [AGGR]	5
Useful luminous flux (Φuse) [AGGR]	2036 lm
Fényszín LED	White

Fénytechnikai adatok

Beam angle	0 °
Gyújtási idő	< 01 s
Bemelegedési idő	< 200 s

LED modul információ

LED-ek száma / modul	8
----------------------	---

Méretetek és súly

Termék súlya	2700 g
Height EPREL [AGGR]	8.0 mm
Length EPREL [AGGR]	121.0 mm
Width EPREL [AGGR]	50.0 mm

Hőmérséklet és működési feltételek

Hőmérséklet-tartomány tároláskor	-30...85 °C
Max. hőmérséklet a tc mérőponton	85 °C
Környezeti hőmérséklet tartomány	-40...+70 °C
Működési hőmérséklet IEC 62717 szerint	55 °C

Élettartam

Kapcsolási ciklusok száma	100000
---------------------------	--------

Termék adatlap

Lumen maintenance factor LMF [AGGR]	96
L70B50 lifetime [AGGR]	100000 h

További termékadatok

Lighting technology used [AGGR]	LED
---------------------------------	-----

Képességek

Dimmelhető	Yes
------------	-----

Tanúsítványok és szabványok

Védettség típusa	IP20
Szabványok	CE/ENEC
Energy efficiency class [AGGR]	E

Logisztikai adatok

Commodity code	85395100000
----------------	-------------

Környezetvédelmi információk

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	23-06-2023
Primary Article Identifier	4062172064330
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Download Data

File	
	Certificates PL BRICK BA BAR CLE VDE ENEC 40045382 210723

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Termék adatlap

Logisztikai adatok

Termékkód	Termékmegnevezés	Csomagolás (darab/egység)	Méretek (hosszúság x szélesség x magasság)	Térfogat	Bruttó súly
4062172064330	PL-BRICK HP-Z2 1900 722 2X4	Karton 120	350 mm x 280 mm x 157 mm	15.39 dm ³	3686.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Lemondás

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.