


STARTERcable 1200A

**Up to 1200A peak amps**

For transferring the charging current to start even almost completely discharged batteries

**600A Continuous amp rating**

For permanent current transmission and protection against overheating, a continuous amp rating of 600A is given

**Up to 9.5 liter**

Suitable for starting vehicles with a petrol or diesel engine with a capacity of up to 9.5L

**2-year OSRAM Guarantee***

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

**Classic starter cables from OSRAM**

With a range of OSRAM starter cables, motorcycle, car, commercial vehicle and truck drivers now have a quick and easy solution to rapidly transfer the battery power between a donor and a receiver vehicle and thus become ready to drive again.

The OSRAM BATTERYstart STARTER CABLE 1200A is a high quality starter cable designed for professional and private use. The cables are made of copper coated aluminum which reduces the resistance of the cable and allows a constant and effective transmission of the charge. The starter cable has a length of 5 meters with a cross-sectional area of 50mm². Thanks to the length and the cross-sectional area, it is possible to start vehicles with petrol and diesel engines with up to 9.5 liters of displacement, as a peak amp of up to 1200A can be achieved, at the same time a continuous amp rating of 600A is given. It is suitable for voltages of 12V and 24V. To prevent high wear and tear, the OSRAM BATTERYstart STARTER CABLE 1200A is sheathed in flexible yet durable PVC, the insulated clamps and handles provide additional safety and durability. The different colors of the cables and the handles on the clamps reduce the risk of mixing up the positive and negative terminals and thus the risk of incorrect connection to the battery. The storage bag included in the scope of delivery allows the cables to be stored tidy and, in a space-saving manner. Conveniently, the operating

instructions are also attached to the back of the storage bag and are thus quickly at hand. OSRAM offers a 2-year guarantee* on this product.

Product family datasheet

Technical data

	Product information	Electrical Data		Physical Attributes & Dimensions
Product description	Engine type	Peak Amps	Continuous amp rating	Length
STARTERcable 1200A	Diesel / Petrol	1200A	600 A	340 mm

	Dimensions & weight			
Product description	Width	Height	Cross section area	Engine size
STARTERcable 1200A	250 mm	105 mm	50 mm ²	≤ 9.5L

	Colors & materials	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Product description	Material	Candidate list substance 1	Declaration no. in SCIP database
STARTERcable 1200A	Copper Coated Aluminum	No declarable substances contained	No declarable substances contained

Product family datasheet

Legal advice

*for precise conditions please refer to:

www.osram.com/am-guaranteeApplication advice: For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.